

## 48 F SM G652D ARMOURED OPTICAL FIBRE CABLE

### 1. FIBRE PROPERTIES

A. FIBRE TYPE	:	Single Mode G652 D
B. ATTENUATION @ 1310 nm	:	≤ 0.35 dB/Km
@ 1550 nm	:	≤ 0.22 dB/Km
C. CABLE CUT-OFF WAVELENGTH	:	≤ 1260 nm
D. MODE FIELD DIAMETER @ 1310 nm	:	9.2 ± 0.5µm
E. CLAD DIAMETER	:	125 ± 0.7 µm
F. CORE CLAD CONCENTRICITY ERROR	:	≤ 0.60 µm
G. CLAD NON-CIRCULARITY	:	≤ 1%
H. COATING DIAMETER	:	245 ± 10 µm
I. CHROMATIC DISPERSION	:	
Between 1270-1340 nm	:	≤ 5.3 ps/nm.km
1285-1330 nm	:	≤ 3.5 ps/nm.km
@ 1550 nm	:	≤ 18.0 ps/nm.km
J. ZERO DISPERSION WAVELENGTH	:	1300-1324 nm
K. ZERO DISPERSION SLOPE	:	≤ 0.092 ps/nm <sup>2</sup> .Km
L. POLARISATION MODE DISPERSION	:	≤ 0.2 ps/root km

### 2. MECHANICAL & ENVIRONMENTAL PROPERTIES

A. MAX. OPERATING TENSION	:	1500 Newton
MAX INSTALLATION TENSION	:	2700 Newton
B. CRUSH RESISTANCE	:	4000 Newton/100 mm
C. MINIMUM BENDING RADIUS	:	250 mm
D. MAX. OPERATING/ INSTALLATION TEMPERATURE	:	- 30 °C to + 70 °C

### 3. PHYSICAL & DIMENSIONS PROPERTIES

NO. OF FIBRES	48F
FIBRE COLOUR IN LOOSE TUBE	BLUE, ORANGE, GREEN, BROWN, GREY, WHITE, RED, BLACK, YELLOW, VIOLET, PINK & AQUA
LOOSE TUBE COLUR & SEQUENCE	BLUE, ORANGE, GREEN, BROWN, DUMMY-1 & DUMMY-2
CENTRAL MEMBER	FRP ROD
DIAMETER OF LOOSE TUBE	2.0 mm Nominal
OUTER SHEATH THICKNESS	1.8 mm Nominal
ARMOURING	CORRUGATED STEEL TAPE ARMOUR
CABLE DIAMETER	12.5 ± 0.8 mm
WEIGHT OF CABLE	125 ± 15 Kg/Km
PRINTING ON CABLE	AS PER CUSTOMER REQUIREMENT
STANDARD LENGTH	2/3/4 Km + 10% and 10% Non standard length more than 500 meters

### CONSTRUCTION OF CABLE

- OUTER SHEATH (H.D.P.E.)
- W.S. TAPE
- W.S. YARN
- F.R.P. ROD
- LOOSE TUBE WITH FIBRES
- CORRUGATED STEEL TAPE ARMOUR
- RIP CORD

